


**Corrugated Stainless Steel Flexible
Water Heater/Softener Connectors
Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

- DESIGN FEATURES: Mega-flow SUPER Water-flex™
- 304 Series Stainless Steel
- True .72" ID
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * IAPMO R&T Tested & Certified
- * UPC (USA)
- * cUPC (Canada)
- * ASME A112.18.6
- * NSF-61 (IAPMO Certified to ANSI/NSF section 9)
- *  Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Length</u>
FF-6	3/4" FIP x 3/4" FIP	6"
FF-12	3/4" FIP x 3/4" FIP	12"
FF-15	3/4" FIP x 3/4" FIP	15"
FF-18	3/4" FIP x 3/4" FIP	18"
FF-24	3/4" FIP x 3/4" FIP	24"
FF-36	3/4" FIP x 3/4" FIP	36"
FF-48	3/4" FIP x 3/4" FIP	48"



Product Submittal

Job Name: _____

Date: _____

Model# _____ Quantity: _____

Architect/Contractor: _____