



**Corrugated Stainless Steel Flexible
Water Heater/Softener Connectors
Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

- DESIGN FEATURES: Mega-flow SUPER Water-flex™
- 304 Series Stainless Steel
- True .72" ID
- Male end union swivel
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Eliminates need for male nipple
- Bright annealed

COMPLIANCES/LISTINGS:

- * IAPMO R & T Tested & Certified
- * UPC (USA)
- *cUPC (Canada)
- * ASME A112.18.6
- * NSF-61 (IAPMO Certified to ANSI/NSF section 9)
- * **W** Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Length</u>
FM-15	¾" MIP x ¾" FIP	15"
FM-18	¾" MIP x ¾" FIP	18"
FM-24	¾" MIP x ¾" FIP	24"
Male End Union Swivel		



<u>Product Submittal</u>	
Job Name:	_____
Date:	_____
Model#	Quantity: _____

Architect/Contractor: _____	