



**Corrugated Stainless Steel Flexible
Tankless/Faucet/Filtration Connector
Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Flexible water connectors to tankless/ faucet/ filtration systems.

- DESIGN FEATURES:
- 304 Series Stainless Steel
- 7/16" OD
- High Flow High Efficiency
- Flows 100% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 250 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * IAPMO R & T Tested & Certified
- * UPC (USA)
- * cUPC (Canada)
- * ASME A112.18.6
- * NSF 61 (IAPMO Certified to ANSI/NSF section 9)
- * **W** Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Lengths</u>
S-01	3/8" Comp x 3/8" Comp	16", 20", 48", 60"
S-03	1/2" FIP x 3/8" Comp	12", 16", 20", 30"
S-01 and S-03 Models come with 7/16" OD Corrugated Stainless Steel Flexible Tube		



Product Submittal

Job Name: _____

Date: _____

Model# _____ Quantity: _____

Architect/Contractor: