



**Corrugated Stainless Steel Flexible  
Water Heater/Softener Connectors  
Specification Sheet**

**SPECIFICATION:**

Furnish and install Corrugated Stainless Steel Water Heater (80+ gal.) & Softener Connectors

- DESIGN FEATURES:
- 304 Series Stainless Steel
- True 31/32" ID
- Flows 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright Annealed

**COMPLIANCES/LISTINGS:**

- \* IAPMO R & T Tested & Certified
- \* UPC (USA)
- \*cUPC (Canada)
- \* ASME A112.18.6
- \* NSF-61 (IAPMO Certified to ANSI/NSF section 9)
- \* **W** Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWC-1 x 12	1" FIP x 1" FIP	12"
SWC-1 x 18	1" FIP x 1" FIP	18"
SWC-1 x 24	1" FIP x 1" FIP	24"



Product Submittal

Job Name: \_\_\_\_\_

Date: \_\_\_\_\_

Model# \_\_\_\_\_ Quantity: \_\_\_\_\_

\_\_\_\_\_  
Architect/Contractor: \_\_\_\_\_