



**Corrugated Stainless Steel Flexible  
Water Heater/Softener Connectors  
Specification Sheet**

**SPECIFICATION:**

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

- DESIGN FEATURES: Mega-flow SUPER Water-flex™
- 304 Series Stainless Steel
- True .72" Tube ID
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Copper Sweat Sleeve at one end
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Easy Installation
- Bright annealed

**COMPLIANCES/LISTINGS:**

- \* IAPMO R & T Tested & Certified
- \* UPC (USA)
- \* cUPC (Canada)
- \* ASME A112.18.6
- \* NSF 61 (IAPMO Certified to ANSI/NSF section 9)
- \* **W** Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Length</u>
----------------	--------------------	---------------

SWT x Fem	3/4" Copper Sweat x 3/4" FIP	15"
SWT x Fem	3/4" Copper Sweat x 3/4" FIP	18"
SWT x Fem	3/4" Copper Sweat x 3/4" FIP	24"

Copper Sweat x FIP for more permanent installations



Product Submittal

Job Name: \_\_\_\_\_

Date: \_\_\_\_\_

Model# \_\_\_\_\_ Quantity: \_\_\_\_\_

\_\_\_\_\_  
Architect/Contractor: \_\_\_\_\_