



**Corrugated Stainless Steel Flexible Connectors**  
**“Push to connect”**  
Specification Sheet

### SPECIFICATION:

Furnish and install Corrugated Stainless Steel Connectors for residential water heater/softener

**Model PTC34-JG**

**3/4” FIP x 3/4” John Guest “Push to connect”**

**DESIGN FEATURES: Mega-flow SUPER Water-flex™**

- 304 Series Stainless Steel
- Maintains optimum flow – No Restriction
- True .72” ID
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure 850 psi
- 100% Leak Tested
- Limited Lifetime Warranty
- Temperature rating 40 – 250 degrees F
- Easy Installation

### COMPLIANCES/LISTINGS:

- \* IAPMO Listed
- \* UPC/cUPC
- \* ASME A112.18.6
- \* IAPMO Tested to NSF 61



Product Submittal

Job Name: \_\_\_\_\_

Date: \_\_\_\_\_

Model# \_\_\_\_\_ Quantity: \_\_\_\_\_

\_\_\_\_\_  
Architect/Contractor: \_\_\_\_\_