



**Corrugated Stainless Steel Flexible
Toilet & Bidet Connectors
Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Flexible water closet connectors

- DESIGN FEATURES:
- 304 Series Stainless Steel
- Chrome plated brass Ballcock
- High Flow High Efficiency
- Flows approx 100% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 250 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * IAPMO R & T Tested & Certified
- * UPC (USA)
- * cUPC (Canada)
- * ASME A112.18.6
- * NSF 61 (IAPMO Certified to ANSI/NSF section 9)
- * **W** Watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Lengths</u>
T-07	7/8" Ballcock x 1/2" FIP	9", 12"
T-06	7/8" Ballcock x 3/8" Comp	9", 12"
Chrome Plated Brass Ballcock for Toilet & Bidet Installations		



Product Submittal

Job Name: _____

Date: _____

Model# _____ Quantity: _____

Architect/Contractor: _____

