


**Corrugated Stainless Steel Flexible
Water Purification / Softener Connectors
Specification Sheet**

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Full Port Water Softener Connectors

- **DESIGN FEATURES: Mega-flow SUPER Water-flex™**
- 304 Series Stainless Steel
- True .72" ID on ¾" models
- True 31/32" ID on 1" models
- No reduction necessary for easiest installation
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Operate appliance at maximum efficiency
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Custom Design – Installs Direct from Appliance to Supply line
- Bright annealed

COMPLIANCES/LISTINGS:

- * IAPMO Listed
- * UPC (USA)
- * cUPC (Canada)
- * ASME A112.18.6
- * NSF 61 (IAPMO Certified to ANSI/NSF section 9)
- *  watermark for Australia and New Zealand

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWC 114 x 1"	1 ¼" FIP x 1" FIP	12", 15", 18", 24"
SWC 114 x ¾"	1 ¼" FIP x ¾" FIP	15, 18, 24"

Designed and manufactured specifically to save time & money on the installation without reducing the flow!



Product Submittal

Job Name: _____

Date: _____

Model# _____ Quantity: _____

Architect/Contractor: _____